



used for: D-SUB FILTER

POS.	A ^{-0.76}	B ^{-0.25}	C	PART NO.
9	31.19	16.46	25.00 ^{+0.12} / _{-0.13}	242A15030X
15	39.52	24.79	33.30 ^{+0.15} / _{-0.1}	242A15040X
25	53.42	38.50	47.04 ^{+0.13}	242A15050X
37	69.70	54.96	63.50 ^{+0.13}	242A15060X

- NOTES:**
1. METAL SHELLS: STEEL; TIN PLATED
 2. INSULATOR: PBTP GF UL 94 V-0
 3. CONTACTS: COPPER ALLOY
 4. PLATING: HARD GOLD OVER NICKEL
 5. PCB-SNAP: COPPER ALLOY; TIN PLATED
PCB HOLE $\phi 3.1 \pm 0.1$; PCB THICKNESS $t = 1.6\text{mm}$
 6. CAPACITANCE: $1300\text{pF} \pm 20\%$
 7. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
 8. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
 9. = CRITICAL DIMENSION: SPC

DO NOT ALTER CAD DRAWING BY HAND
OWNERSHIP AND COPYRIGHT OF CONEC GMBH
WRITTEN PERMISSION
BE PASSED ON TO A THIRD PARTY WITHOUT
REPRODUCED IN ANY WAY, AND MAY NOT
THIS DRAWING MAY NOT BE COPIED OR

CONEC CORPORATION BRAMPTON, ONTARIO		tolerance	2:1 (5:1)
		material	SEE NOTES
		title	D-FILTER FEMALE P-TYP 9-37pos. PIN 5.8mm WITH THREADED SPACER CLIP
1996	date	name	DIN-A
08.05.	drawn	Barcinski	3
08.05.	appd.	Mickenbecker	sh:1/1
	norm	DIN 41652	
	d-old		
		dwg no:	24K11Y8A
		product no:	SEE TABLE

CONEC®

rev.	description	date	name