




toggle shown in pos. a



P.C. MOUNTING



CONTACT ARRANGEMENT

code for x	function	toggle in pos. a	toggle in pos. c
D	On-On	2-3	1-2
F	On-Mom	2-3	1-2

code for x	function	toggle in pos. a	toggle in pos. b	toggle in pos. c
E	On-Off-On	2-3	open	1-2
G	Mom-Off-Mom			
H	On-Off-Mom			

Specifications:

- Contact rating:** max.: 0.4VA, 48V AC or DC, 50mA
 min.: 1µA, 20mV AC or DC
Contact resistance: 50mOhm max. at 2-4V DC, 100mA
Insulation resistance: 1000MOhm min.
Dielectric strength: 500V RMS
Operating temperature: -20°C to +85°C
Electrical life: 40 000 make-and-break cycles
Soldering conditions: wave-soldering: 260 +/-5°C, 5 +/-1sec.
Protection: IP67
Material: Actuator: brass, chrome plated
 Bushing / housing: steel
 Case: glass filled PBT (UL94V-0)
 Contact / terminals: phosphor bronze, gold plated over nickel barrier



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm	Date	Name
	03/14	dr

ATE 1 x

knitter-switch

30 30 52

Page

1/1

Modifications	Date	Name
---------------	------	------