

Power management: linear and switching regulators and voltage references

Selection guide



December 2005

www.st.com/powermanagement
www.st.com/vregs
www.st.com/viper



Linear voltage regulators

Part number composition (family code + suffix)

Std positive	Std negative	Low drop	Very low drop
LM C 38 P	LM C 37 P	L4941 PS	L4940 PVVS
LM C 50 P	L79 VVTCPS	LD1117 PVVC S	LD1580 PVVS
LM C 23 P	L79L VVTCPS	KD1083 PVVS	LD29080 PVVS
LM C 17 PS		LD1084 PVVS	LD29150 PVVS
LM C 17 MPS		LD1085 PVVS	LD29300 PVVS
LM C 17L PS		LD1086 PVVS	LD2979 PVVS
LM723 PS		LD1117A PVVS	LD3985 PVVS
L78S VVTC P		LK112 PVVS	LK115 PVV
L78 VVTC PS		LK112S PVVS	STC2 PVVS
L78M VVTC PS		KD1084 TPVVS	L4931 TPVVS
L78L VVTC PS		LD1585 TPVVS	L4987 TPVVS
			LD2980 TPVVS
			LD2981 TPVVS
			LD2982 TPVVS
			LD2985 TPVVS
			LM2931 TPVVS
			KF VVTP S
			LE VVTP S
			LF VVTP S

P: Package suffix
 VV: Voltage suffix
 T: Tolerance

C: Temperature class
 S: Shipment packaging (see table)

Packages suffixes

Package	Very low drop	Low drop	Standard positive and negative	
			L78/79 series	LM series
D ² PAK	D2T	D2T	D2T	D2T
D ² PAK/A	D2M	D2M		
DIP				N
DPAK	DT	DT	DT	DT
Flip-Chip5	J			
P ² PAK	P2T			
PENTAWATT	V5V			
PPAK	PT			
SO-8	D	D	D	D
SOT223		S		
SOT23-5L	M	M		
SOT-89	U		U	
SPAK-5L	K5			
SPAK-7L	K7			
TO-220	V	V	V	T*
TO-220FP	P	P	P	
TO-3			T	K
TO-92	Z		Z	Z
TSOT23-5L	G			

* SP for LM337

Shipment suffixes

Tube	No suffix
T & R	13TR, 013TR, TR, -TR, R, -R
Amopack	AP, -AP

Low drop linear voltage regulators

Family	I_o max [A]	Regulated output voltage [V]														V_d [V]	T_{ol} [%]	Packages																	
		1.2	1.3	1.5	1.6	1.7	1.8	2.1	2.5	2.7	2.8	2.85	3	3.2	3.3			3.6	3.8	4	5	6	8	9	12	Adj	D ² PAK	D ² PAK / A	DPAK	SOT23	SOT23-5L	SO-8	TO-220	TO-220FP	
KD1083	7.5			■			■		■			■												1.25 to 8.5	1.4	2	■							■	
KD1084				■			■		■		■				■	■			■						1.25 to 15	1.3	2	■	■	■				■	
KD1084A				■			■		■		■				■	■			■						1.25 to 15	1.3	1	■	■	■				■	
LD1084	5			■			■		■		■				■	■			■						1.25 to 28	1.3	1	■	■					■	
LD1585				■			■		■		■				■	■			■		■	■	■		1.25 to 28	1.2	1	■	■					■	
LD1085C				■			■		■		■				■	■			■		■	■	■		1.25 to 28	1.3	2			■					
LD1085				■			■		■		■				■	■			■		■	■	■		1.25 to 28	1.3	1	■	■					■	
LD1086	1.5			■			■		■		■				■	■			■		■	■	■		1.25 to 28	1.3	1	■	■	■				■	
L4941																										0.25	4	■		■					■
LD1117A	1						■		■		■				■	■			■						1.25 to 15	1.1	2			■	■			■	
LD1117xx			■				■		■		■				■	■			■						1.25 to 15	1.1	1			■	■			■	
LD1117xxC	0.8						■		■		■				■	■			■						1.25 to 15	1.1	2			■	■			■	
LK112S (*)	0.2			■	■	■	■		■		■				■	■			■		■	■	■			0.35	2					■			
LK112	0.15			■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			0.29	2					■			

* All voltages from 1.3 to 5V with a 0.1V step, are available upon request

■ On request

Dual and triple output linear voltage regulators

Family	I_o max [A]	Output 1							V_d [V]	T_{ol} [%]	I_o max [A]	Output 2						V_d [V]	T_{ol} [%]	I_o max [A]	Output 3			Packages										
		Output voltage [V]										Output voltage [V]									Output voltage [V]			PPAK	SPAK	DFN								
		1.5	1.8	2.5	2.6	2.8	3	3.3				1.5	1.8	2.5	2.8	3	3.3				Adj	8	V_d [V]				T_{ol} [%]							
ST2L05		■	■	■		■	■	■		■	■	■	■	■	■	1.25 to 3	1.1	3										■	■	■				
ST2L01	1															1.25 to 3	1.1	2										■	■					
LDRxxyy	0.5		■	■				■									0.45	5										■	■					
ST3L01	1.2				■																					0.2		■						■

■ On request

Application specific linear voltage regulators

Part number	Description	V_{in} [V]			V_{out} [V]			V_d [mV]	I_o [max] [A]	T_{op} [°C]		Short circuit protection	Thermal shutdown	Disable pin	Package
		Min	Typ	Max	Min	Typ	Max			Min	Max				
LNBK10SP	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-10	
LNBK11SP	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-10	
LNBK12SP	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-10	
LNBK13SP	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-10	
LNBK14SP	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-10	
LNBK15SP	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-10	
LNBK16SP	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-10	
LNBK20D2	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		SO-20	
LNBK20PD	LNB supply and control voltage regulator (parallel interface)			27		13 to 18		0.4	-40	125	■	■		PowerSO-20	
LNBP10SP	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-10	
LNBP11SP	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-10	
LNBP12SP	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-10	
LNBP13SP	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-10	
LNBP14SP	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-10	
LNBP15SP	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-10	
LNBP16SP	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-10	
LNBP20PD	LNB supply and control voltage regulator (parallel interface)			25		13 to 18		0.5	-40	125	■	■		PowerSO-20	
PB137ACV	Positive voltage regulator for battery charger			40		13.7		1.5	0	150	■	■		TO-220	
ST1534LD	500mA smart LDO					3.3		0.55	0	85	■	■		SO-8	

Step-up switching voltage regulators

Part number	Description	Topology	V _{in} [V]		V _{out} [V]			Adjustable	I _o [max] [A]	I _q [μA]	f [kHz] max	Efficiency [%]	Peak current limitation	Disable pin	T _{op} [°C]		Package
			Min	Max	Min	Typ	Max								Min	Max	
L6920	0.5A step up converter	Step-up	0.6	5.5	2		5.2	■		11	1MHz		1A	■			TSSOP8
L6920DB	0.5A step up converter	Step-up	0.6	5.5	1.8		5.2	■		11	1MHz		0.8A	■			MSOP8
ST5R25M	Micropower VFM step-up DC/DC converter	Step-up	1.2	5.5		2.5			0.1		150	87			-25	85	SOT23-5L
ST5R28M	Micropower VFM step-up DC/DC converter	Step-up	1.2	5.5		2.8			0.1		150	87			-25	85	SOT23-5L
ST5R30M	Micropower VFM step-up DC/DC converter	Step-up	1.2	5.5		3			0.1		150	87			-25	85	SOT23-5L
ST5R30U	Micropower VFM step-up DC/DC converter	Step-up	1.2	5.5		3			0.1		150	87			-25	85	SOT-89
ST5R33M	Micropower VFM step-up DC/DC converter	Step-up	1.2	5.5		3.3			0.1		150	87			-25	85	SOT23-5L
ST5R50M	Micropower VFM step-up DC/DC converter	Step-up	1.2	5.5		5			0.1		150	87			-25	85	SOT23-5L

Step-down switching voltage regulators

Part number	Description	Topology	V _{in} [V]		V _{out} [V]			Adjustable	I _q [μA]	f [kHz] max	Peak current limitation [A]	Disable pin	T _{op} [°C]		Package
			Min	Max	Min	Typ	Max						Min	Max	
L6925D	Up to 0.8A high efficiency synchronous regulator	Step-down	2.7	5.5	0.6		5.5	■	25	600. synch up to 1400	1.2				MSOP8
L6926	Up to 0.8A high efficiency synchronous regulator	Step-down	2	5.5	0.6		5.5	■	25	600. synch up to 1400	1.2	■			MSOP8
L6926D	Up to 0.8A high efficiency synchronous regulator	Step-down	2	5.5	0.6		5.5	■	25	600. synch up to 1400	1.2	■			VFSON8
L6928D	Up to 0.8A high efficiency synchronous regulator	Step-down	2	5.5	0.6		5.5	■	25	1400. synch up to 2000	1.2	■			MSOP8
L6902	1A switching regulator	Step-down	8	36	1.23		35	■	3000	250	2.5				SO-8
L5970	1A switching regulator	Step-down	4.4	36	0.5		35	■	2500	250. synch up to 700	1.87	■			SO-8
L5970A	1A switching regulator	Step-down	4.4	36	0.5		35	■	2500	500. synch up to 700	1.87	■			SO-8

Step-down switching voltage regulators cont'd.

Part number	Description	Topology	V _{in} [V]		V _{out} [V]			Adjustable	I _q [μA]	f [kHz] max	Peak current limitation [A]	Disable pin	T _{op} [°C]		Package
			Min	Max	Min	Typ	Max						Min	Max	
L5972	1.5A switching regulator	Step-down	4.4	36	1.23		35	■	2500	250. synch up to 700	2.5				SO-8
L5973A	1.5A switching regulator	Step-down	4.4	36	0.5		35	■	2500	500. synch up to 700	2.3	■			PowerSO-8
L5973	2A step down switching regulator	Step-down	4.4	36	0.5		35	■	2500	250. synch up to 700	3	■			PowerSO-8
L296	4A switching regulator	Step-down	9	46	5.1		40	■	30000	Up to 200	4.5	■			MW15
L4960	2.5A switching regulator	Step-down	9	46	5.1		40	■	15000	Up to 200	3				HW7
L4962	1.5A switching regulator	Step-down	9	46	5.1		40	■	15000	Up to 200	2	■			HW7, PDIP16
L4963	1.5A switching regulator	Step-down	9	46	5.1		40	■	15000	Free running	3.5				PDIP18, SO-20
L4970	10A switching regulator	Step-down	12	50	5.1		50	■	13000	Up to 500	13				MW15
L4971	1.5A switching regulator	Step-down	8	55	3.3		50	■	2500	Up to 300	2.5	■			DIP8, SO-16W
L4972	2A switching regulator	Step-down	12	50	5.1		40	■	13000	Up to 200	2.8				PDIP20, SO-20
L4973	3.5A switching regulator	Step-down	8	55	0.5		50	■	2700	Up to 300	4.5	■			PDIP18, SO-20
L4974A	3.5A switching regulator	Step-down	12	50	5.1		40	■	13000	Up to 200	4.75				MW15
L4975A	5A switching regulator	Step-down	12	50	5.1		40	■	13000	Up to 500	6.5				MW15
L4976	1A switching regulator	Step-down	8	55	0.5		50	■	2500	Up to 300	2	■			DIP8, SO-16W
L4977	7A switching regulator	Step-down	12	50	5.1		40	■	13000	Up to 500	9.5				MW15
L4978	2A switching regulator	Step-down	8	55	3.3		50	■	2500	Up to 300	3	■			DIP8, SO-16W
ST730ACD	5V DC-DC converter current mode PWM regulator	Step-down	4	11		5			800	200	2	■	0	70	SO-8
ST750ACD	Adjustable DC-DC converter current mode PWM regulator	Step-down	4	11		1.25 · V _{in}		■	800	200	2	■	0	70	SO-8
ST763ABD	3.3V current mode PWM DC-DC converters	Step-down	3.3	11		3.3			600	200	2	■	-40	85	SO-8
ST763ABN	3.3V current mode PWM DC-DC converters	Step-down	3.3	11		3.3			600	200	2	■	-40	85	DIP-8
ST763ACD	3.3V current mode PWM DC-DC converters	Step-down	3.3	11		3.3			600	200	2	■	0	70	SO-8
ST763ACN	3.3V current mode PWM DC-DC converters	Step-down	3.3	11		3.3			600	200	2	■	0	70	DIP-8
ST1S03PMR	Adjustable step-down DC-DC converter		3	16		0.8 - 0.87 V _{in}		■	2500	1500	1.65				DFN6 (3x3mm)

Inverting switching voltage regulators

Part number	Description	Topology	V _{in} [V]		V _{out} [V] typ	Adjustable	I _o [μA]	f [kHz] max	Peak current limitation [A]	Disable pin	T _{op} [°C]		Package
			Min	Max							Min	Max	
ST735CD	-5 inverting negative output current mode PWM regulator	Inverter	4	6.2	-5		800	160	2	■	-40	125	SO-8
ST735SCD	300kHz -5V inverting negative output current mode PWM regulator	Inverter	4	6.2	-5		800	300	2	■	-40	125	SO-8
ST735TCD	300kHz ADJ inverting negative output current mode PWM regulator	Inverter	3.5	9	-9 to -3.5	■	800	300	2	■	-40	125	SO-8
ST755CD	ADJ inverting negative output current mode PWM regulator	Inverter	4	11	-8.7 to -1.7	■	1200	160	2	■	-40	85	SO-8
ST755CN	ADJ inverting negative output current mode PWM regulator	Inverter	4	11	-8.7 to -1.7	■	1200	160	2	■	-40	85	DIP-8

Multifunction: step-up-down inverting switching voltage regulators

Part number	Description	Topology	V _{in} [V]		V _{out} [V] typ	Adjustable	I _o [μA]	f [kHz] max	Peak current limitation [A]	Disable pin	T _{op} [°C]		Package
			Min	Max							Min	Max	
MC34063ABD	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	2.5	33	1.5		-40	85	SO-8
MC34063ABN	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	2.5	33	1.5		-40	85	DIP-8
MC34063ACD	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	2.5	33	1.5		0	70	SO-8
MC34063ACN	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	2.5	33	1.5		0	70	DIP-8
MC34063EBD	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	1.5	33	1.5		-40	125	SO-8
MC34063EBN	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	1.5	33	1.5		-40	125	DIP-8
MC34063ECD	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	1.5	33	1.5		0	70	SO-8
MC34063ECN	DC-DC converter control circuits	Step-up-down		50	1.25 to 38	■	1.5	33	1.5		0	70	DIP-8

* Only non inverting version

Application specific switching voltage regulators

Part number	Description	V_{in} [V]		V_{out} [V] typ.		f [kHz]	I_o max [A]	T_{op} [°C]		Efficiency [%]	Disable pin	Package
		Min	Max	Min	Max			Min	Max			
LNBEH21PD	LNB supply and control IC with step-up converter and I ² C interface. Semi low drop out control voltage regulators	8	15	13	18	220	0.45 to 0.75	-40	125	>90	I ² C	PowerSO-20
LNBH21PD	LNB supply and control IC with step-up converter and I ² C interface. Semi low drop out control voltage regulators	8	15	13	18	220	0.45 to 0.75	-40	125	>90	I ² C	PowerSO-20
LNBH221PD	Double lnb supply and control IC with step-up converter and I ² C interface. Semi low drop out control voltage regulators	8	15	13	18	220	0.5	-40	125	>90	I ² C	PowerSO-36
LNBP21D2	LNBP supply and control IC with step-up converter and I ² C interface	8	15	13	18	220	0.4 to 0.5	-40	125	>90	I ² C	SO-20
LNBP21PD	LNBP supply and control IC with step-up converter and I ² C interface	8	15	13	18	220	0.4 to 0.5	-40	125	>90	I ² C	PowerSO-20
LNBS21PD	LNBP supply and control IC with step-up converter and I ² C interface	8	15	13	18	220	0.4 to 0.5	-40	125	>90	I ² C	PowerSO-20
ST3M01D	Switching & dual outs linear voltage regulators	1.9	3.3	1.9 - 3	3.3		0.02 to 0.02 to 0.2	-40	85	87	■	SO-14
ST3S01PHD	Battery charger IC		16				I _{supply} (max)	-40	125			PowerSO-8
ST619LBD	DC-DC converter regulated 5V charge pump	2	5.5	5	5	500	0.12	-40	85	85	■	SO-8
ST619LBN	DC-DC converter regulated 5V charge pump	2	5.5	5	5	500	0.12	-40	85	85	■	DIP-8
ST662ABD	DC-DC converter from 5V to 12V. 0.03A for flash memory programming supply		6	5	12	400	0.05	-40	85	72	■	SO-8
ST662ABN	DC-DC converter from 5V to 12V. 0.03A for flash memory programming supply		6	5	12	400	0.05	-40	85	72	■	DIP-8
ST662ACD	DC-DC converter from 5V to 12V. 0.03A for flash memory programming supply		6	5	12	400	0.05	0	70	72	■	SO-8
ST662ACN	DC-DC converter from 5V to 12V. 0.03A for flash memory programming supply		6	5	12	400	0.05	0	70	72	■	DIP-8
STLC1PD	LED lamps cluster driver		24				7	-40	125		■	PowerSO-20

PFC controllers

Part number	Description	V _{DD} [V]			I _{CC} [A] nom	Universal input mains	Protection option type	Topology mode	Fsw max	Package
		Min	Nom	Max						
L4981A	Average current mode			19.5	1.6	■	Over current, overvoltage	PWM	200	DIP-20, SO-20
L4981B	Average current mode			19.5	1.6	■	Over current, overvoltage	PWM	200	DIP-20, SO-20
L6561	Transition mode	11		18	4	■	Over current, overvoltage	Transition		DIP-8, SO-8
L6562	Transition mode	10.3	12	22	3.5	■	Overvoltage protection	Transition mode		SO-8, DIP-8
L6563	Advanced transition mode PFC Controller	10.3	12	22	5.5	■	Overvoltage	Transition mode		SO-14

Current mode PWM controllers

Part number	Description	V _{DD} [V]		Max [A] nom	Fsw [kHz] max	Max duty cycle [%] typ	Current limiting mode	Disable pin	Standby pin	Package
		Min	Max							
L5991	Current mode PWM	12	20	1.5	100	93	Pulse, hiccup	■	■	DIP-16, SO-16
L6668	Smart primary controller	9.4	22	0.8	105	75	Peak current mode	■	■	SO-16
UC2842B	Current mode PWM	11	30	1	500	100	Pulse			SO-8, DIP-8
UC2843B	Current mode PWM	8.2	30	1	500	100	Pulse			SO-8, DIP-8
UC2844B	Current mode PWM	11	30	1	500	50	Pulse			SO-8, DIP-8
UC2845B	Current mode PWM	8.2	30	1	500	50	Pulse			SO-8, DIP-8
UC3842B	Current mode PWM	11	30	1	500	100	Pulse			SO-8, DIP-8
UC3843B	Current mode PWM	8.2	30	1	500	100	Pulse			SO-8, DIP-8
UC3844B	Current mode PWM	11	30	1	500	50	Pulse			SO-8, DIP-8
UC3845B	Current mode PWM	8.2	30	1	500	50	Pulse			SO-8, DIP-8

Resonant controllers

Part number	Description	V _{DD} [V]		Max [A] nom	Topology	Current limiting mode	Disable pin	Standby pin	Package
		Min	Max						
L6565	Resonant controller	10.3	18	0.4	Quasi resonant	Pulse, hiccup	■		SO-8, DIP-8
L6598	Resonant controller	10.3	18	0.45	Resonant	Pulse, hiccup	■		SO-16, DIP-16

Voltage mode PWM controllers

Part number	Description	V _{DD} [V]		Max [A] nom	F _{sw} [kHz] max	Max duty cycle [%]	Topology	Current limiting mode	Disable pin	Standby pin	Package
		Min	Max								
SG3524	Voltage mode PWM	8	40	0.1	300	45	Voltage mode	Pulse		■	SO-16, DIP-16
SG2525	Voltage mode PWM	8	35	0.5	500	49	Voltage mode	Pulse	■	■	SO-16, DIP-16
SG3525	Voltage mode PWM	8	35	0.5	500	49	Voltage mode	Pulse	■	■	SO-16, DIP-16

Offline converters

Part number	Description	V _{CC} [V]		Bv _{DSS} [V]	R _{DS(on)} [Ω]		I _o [A]	F _{sw} [kHz]	Switching frequency mode	Max duty cycle typ	Topology	Current limiting mode	Standby pin	Package
		Min	Max		min	max								
L6590L	Off-line switching converter	7	16.5	700	16	0.55	65	Internally fixed	70	Buck, buck-boost, fly-back	Pulse	Frequency reduction	DIP-8	
L6590D	Off-line switching converter	7	16.5	700	16	0.55	65	Internally fixed	70	Buck, buck-boost, fly-back	Pulse	Frequency reduction	SO-16	
L6590AN	Off-line switching converter	7.5	15.5	700	16	0.55	65	Internally fixed	70	Buck, buck-boost, fly-back	Pulse	Frequency reduction	DIP-8	
VIPer12AS	SMPS primary I.C.	9	38	730	30	0.32	60	Internally fixed	90	Buck, buck-boost, fly-back	Pulse	Burst mode	SO-8	
VIPer12ADIP	SMPS primary I.C.	9	38	730	30	0.32	60	Internally fixed	90	Buck, buck-boost, fly-back	Pulse	Burst mode	DIP-8	

Offline converters cont'd.

Part number	Description	V _{CC} [V]		B _{VPSS} [V]	R _{DS(on)} [Ω]	I _o [A]	F _{SW} [kHz]	Switching frequency mode	Max duty cycle typ	Topology	Current limiting mode	Standby pin	Package
		Min	Max	Min	Max	Min	Typ						
VIPer22AS	SMPS primary I.C.	9	38	730	30	0.56	60	Internally fixed	90	Buck, buck-boost, fly-back	Pulse	Burst mode	SO-8
VIPer22ADIP	SMPS primary I.C.	9	38	730	30	0.56	60	Internally fixed	90	Buck, buck-boost, fly-back	Pulse	Burst mode	DIP-8
VIPer20	SMPS primary I.C.	9	15	620	16	0.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer20(022Y)	SMPS primary I.C.	9	15	620	16	0.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer20DIP	SMPS primary I.C.	9	15	620	16	0.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	DIP-8
VIPer20A	SMPS primary I.C.	9	15	700	18	0.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer20A(022Y)	SMPS primary I.C.	9	15	700	18	0.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer20ADIP	SMPS primary I.C.	9	15	700	18	0.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	DIP-8
VIPer20ASP	SMPS primary I.C.	9	15	700	18	0.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PowerSO-10
VIPer50	SMPS primary I.C.	9	15	620	5	1.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer50(022Y)	SMPS primary I.C.	9	15	620	5	1.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer50A	SMPS primary I.C.	9	15	700	5.7	1.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer50A(022Y)	SMPS primary I.C.	9	15	700	5.7	1.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer50ASP	SMPS primary I.C.	9	15	700	5.7	1.5		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PowerSO-10
VIPer53DIP	Offline primary switch	9.3	17	620	1	1.6		Externally settable up to 300kHz	90	Buck, buck-boost, Fly-back		Burst mode	DIP-8
VIPer53SP	Offline primary switch	9.3	17	620	1	1.6		Externally settable up to 300kHz	90	Buck, buck-boost, fly-back		Burst mode	PowerSO-10
VIPer53EDIP	Offline primary switch	9.3	17	620	1	1.6		Externally settable up to 300kHz	90	Buck, buck-boost, fly-back		Burst mode	DIP-8
VIPer53ESP	Offline primary switch	9.3	17	620	1	1.6		Externally settable up to 300kHz	90	Buck, buck-boost, fly-back		Burst mode	PowerSO-10
VIPer100	SMPS primary I.C.	9	15	700	2.5	3		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer100(022Y)	SMPS primary I.C.	9	15	700	2.5	3		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer100A	SMPS primary I.C.	9	15	700	2.8	3		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer100A(022Y)	SMPS primary I.C.	9	15	700	2.8	3		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PENTAWATT H.V.
VIPer100ASP	SMPS primary I.C.	9	15	700	2.8	3		Externally settable up to 200kHz	90	Buck, buck-boost, fly-back	Pulse	Burst mode	PowerSO-10

Voltage references

Micropower

Part number	Description	Technology	Precision [%]	Cathode to anode voltage [V]		Reference voltage V_{ref} [V]	Temp. coef. of V_{ref} T_C max [°C]	Operating cathode current [mA]		Static impedance R_{ka} max [Ω]	Line regulation max [mV]	Load regulation max [mV]	Quiescent current typ [mA]
				V_{ka} min	V_{ka} max			I_K min	I_K max				
TS4040-2.5	2.5V micropower shunt voltage reference	BiCMOS	2 - 1			2.5	150	0.065	15	0.6			
TS4041-1.2	1.225V micropower shunt voltage reference	BiCMOS	2 - 1 - 0.5			1.225	150	0.065	12	0.5			
TS431	Low voltage adjustable shunt reference	BiCMOS	2 - 1 - 0.5	1.24	6	1.24	100	0.06	30	0.4			
TS432	1.24V adjustable shunt voltage reference	BiCMOS	1 - 0.5	1.24	10	1.24	100	0.06	12	0.5			
TS821	1.225V micropower shunt voltage reference	BiCMOS	2 - 1 - 0.5			1.225	120	0.045	12	0.5			
TS822	2.5V micropower shunt voltage reference	BiCMOS	2 - 1			2.5	100	0.05	15	0.6			
TS824-1.2	High thermal stability micropower shunt voltage reference	BiCMOS	1			1.225	50	0.05	12	0.7			
TS824-2.5	High thermal stability micropower shunt voltage reference	BiCMOS	1 - 0.5			2.5	50	0.06	15	0.6			

General purpose

LM336	2.5V voltage reference	BIPOLAR	2 - 1			2.5		0.4	10	1			
MC1403	2.5V precision serial voltage reference	BIPOLAR	1			2.5	40				4.5	10	1.2
TL1431	Programmable voltage reference	BIPOLAR	0.4 - 0.25	2.5	36	2.5	100	1	100	0.5			
TL431	Programmable voltage reference	BIPOLAR	2 - 1	2.5	36	2.5	100	1	100	0.5			
TS2431	Programmable shunt voltage reference	BiCMOS	2 - 1 - 0.5	2.5	24	2.5	100	1	100	0.75			
TS3431	Programmable shunt voltage reference	BiCMOS	2 - 1 - 0.5	1.24	24	1.24	100	0.5	100	0.4			
TS4431*	Programmable low voltage shunt regulator	BiCMOS	0.5	0.3	10	1.24	100	0	20		5	5	0.1

Thermal sensors

LM334	Three terminal adjustable shunt current source	BIPOLAR	+ / - 6										
LM335	Precision shunt temperature sensor	BIPOLAR	+ / - 3										

* Next releases



© STMicroelectronics - December 2005 - Printed in Italy - All rights reserved

The STMicroelectronics corporate logo is a registered trademark of the STMicroelectronics group of companies. All other names are the property of their respective owners.

For selected STMicroelectronics sales offices fax:

France +33 1 55489569; Germany +49 89 4605454; Italy +39 02 8250449; Japan +81 3 57838216; Singapore +65 6481 5124;
Sweden +46 8 58774411; Switzerland +41 22 9292900; United Kingdom and Eire +44 1628 890391; USA +1 781 861 2678

Full product information at www.st.com

Order code: SGPOWERMAN1105

